



Material Safety Data Sheet

MSDS REPORT

Sample Name: **Cable Firestop Sealing Stuff (Part A)**

Model : JZ-DMT

Client Name: Jingjiang City Jinzhou Marine Equipment Co., Ltd.

Client Address: No.43, Jiangan Road, Xingang Economic Development Zone,
Jingjiang City, Jiangsu, China

Written by Shanghai EBT Test Technology Co.,Ltd.





Material Safety Data Sheet

Section 1-Chemical Product and Company Identification

Sample Name: Cable Firestop Sealing Stuff (Part A)

Company Identification: Jingjiang City Jinzhou Marine Equipment Co., Ltd.

Add: No.43, Jiangan Road, Xingang Economic Development Zone, Jingjiang City, Jiangsu, China

Tel: +86 523-84068635

Fax: +86 523-84068606

Post Code: 214500

Email: Dongliangchen@vip.163.com

Contact Person: Chen Dongliang

Section 2-Hazards Identification

Fatalness grade: In accordance with Directive 2001/58/EC, the sample is not dangerous.

Invasion route: Skin touch, Eyes touch, Ingestion.

Health Hazards: /

Environment hazards: /

Burn & burst danger: No explosion danger.

Section 3-Composition/Information on Ingredients

Pure Admixture

Composition

CAS No.	Chemical Name	Percent
/	Hydrated gypsum	50%
/	Brucite	30%
/	Kaolin	20%

Section 4-First Aid Measures

Skin touch: Resin with plenty of water. Remove and isolate the contaminated clothes and shoes.

Eyes touch: Flush eyes with flowing water or physiological saline.

Inhalation: No volatile.

Ingestion: Clean oral legacy, get medical assistance.

Section 5-Fire Fighting Measures

Danger characteristic: Flame retardancy.

Extinguishing Media: /

Fire-Fighting method & media: /

Section 6-Accidental Release Measures



Material Safety Data Sheet

Emergency treatment: It is suggested that the staff dress in usual working clothes. Don't touch the spillage directly. Prevent it into restrictive space such as sewer pipes, ditch. Massive divulgence: Build dinking or dig pit to accept. Shift with the pump into the tanker or the special collector, recycle or transport to waste treatment place for handling.

Section 7-Handling and Storage

Handling: With closed operation. To supply with sufficient partial air exhaust. The operating staff must have received special training and abide by the operating regulations. The staff should wear gloves. Keep away from heating sources. No smoking in the workplace. Equip relevant types and quantities of instruments and devices for divulgence handling.

Storage: Keep in the cool, well-ventilated, and dry place. Keep away from fire and heating sources. Keep the container closed. The storage place should equip devices for divulgence and suitable accept materials.

Section 8-Exposure Controls, Personal Protection

Maximum admissible concentration: No standard yet.

Monitoring Methods: /

Engineering Controls: Generally, it is not necessary to have special protection.

Respiratory Protection: No volatile.

Eyes Protection: Wear eyes protector.

Body protection: Wear working protective clothes.

Hands Protection: Wear protective gloves.

Other Protections: /

Section 9-Physical and Chemical Properties

Appearance: Light gray powder.

Melting point:> 1400°C

Flash point: /

Density: 2000kg/m³

Permission of solvent inhalation: /

Solubility: Not soluble.

PH value: /

Section 10-Stability and Reactivity

Stability: Stable.

Distribution of Ban: /

Conditions to Avoid: /

Hazardous Polymerization: /

Section 11-Toxicological Information

Acute Toxicity: /



Material Safety Data Sheet

Sub-acute and Chronic Toxicity: /

Irritation: /

Sensitization: /

Mutagenicity: /

Carcinogenicity: /

Others: /

Section 12-Ecological Information

Eco-toxicity: /

Ecological inert: /

Biodegradable: /

Non-biodegradable: /

Other harmful effects: Be aware of the pollution to water.

Section 13-Disposal Considerations

Nature of waste: /

Waste disposal methods: Refer to National or Local regulations before handling. Recover the former condition of the materials in order to reuse.

Attention abandoned: /

Section 14-Transport Information

Number of dangerous goods: /

UN Number: /

Packaging Mark: /

Packaging Method: Use plastic barrel, etc.

Transport Attentions: The package should be integrated when loaded. Steady and soft handling. Avoid being hit. Examine whether the package of the containers are integrate and tight-closed or not before transport. No divulgence, no collapse, no precipitation or no damage during the course of transportation. Don't put the goods together chief food chemicals. The transport vehicle and ship must be cleaned and sterilized otherwise it is not allowed to assemble articles. The assemble place should keep away from bedroom and kitchen, and the engine room, power and fire source should be isolated from the assemble place. Under the condition of Road Transportation, the driver should drive in accordance with regulated route, don't stop over in the residential area and congested area.

Section 15 -Regulatory Information

Regulatory Information: /

Section 16-Additonal Information

References: /

Guidance departments: /

Data audit unit: /



Material Safety Data Sheet

Laws Help: /

Other Information: The above information is based on the data of which we are aware and is believed to correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

MSDS Creation Date: Aug. 19, 2011

Photograph of sample



*****END*****